

# QF Sliding Access Panel 3103

Ø in.	Pipe Length in.	Slide Length in.	Access Hole	Weight lbs	Galvanized Steel	
					22ga	20ga
6	59.25	18	7 x 14	10.19	Std	
7	59.06		7 x 14	15.18		
8	59.06		7 x 14	17.13		
9	58.75		7 x 14	19.23		
10	58.75		7 x 14	21.36		
11	58.75		7 x 14	23.3		
12	58.75		7 x 14	26.59		Std
13	58.75		7 x 14	28.86		
14	58.75		7 x 14	36.11		
15	58.75		7 x 14	38.56		
16	58.75		7 x 14	41.00		
17	58.75		7 x 14	43.48		
18	58.75		7 x 14	44.99		
20	58.75		7 x 14	49.94		
22	58.75		7 x 14	54.88		
24	58.75		7 x 14	59.92		



### Construction

**Seam:** longitudinal seam is laser welded.

### NOTES:

Reference Nordfab's QF Machine Adapter Technical Data sheet for actual ID and OD dimensions.

Reference Nordfab's QF Clamp Technical Data sheet for dimensional, material, and temperature rating information.

**Ends:** Standard QF end can be changed to Raw ID (RAWID), Raw OD (RAWOD), No Fitting (NF), Hose Adapter (RAWFLEX), Flat Flange (FFL), Angle Flange (ANGFL), or Van Stone (VANSTONE).

**Length:** Product length equals nominal pipe length. Product cannot be made shorter than 36".

# QF Sliding Access Panel 3103

Temperature Rating of Product Components						Additional Notes
° F	QF Sliding Access Panel	Sealants				
1100	Galvanized Steel	Optional - 304SS	3M Scotch Seal Metal Sealant 2084	Optional - Rock River Silicone Sealant	Optional - Red Devil HVAC/R High Temperature Silicone Sealant	Optional - Epoxy - 3M DP 125 Gray Sealant
500						
390						
250						
194						
0						
-40						
-60						

At temperatures ranging between 390° F and 480° F, the zinc-iron alloy layers in galvanized steel will continue to provide a high level of protection from corrosion. However, there may be some peeling, changes in mechanical properties, and reduction in the corrosion protection. Recommended max. service temperature is 390° F.

Rock River Silicone Sealant and Red Devil HVAC/R High Temperature Silicone Sealant are not paintable

304SS:  
bluing may occur at 800° F and above

Compliance / Rating of Product Components		
	Material	Compliance / Rating
QF Sliding Access Panel	Galvanized	ASTM A653 with a G-90 rating
	304SS	Finish meets ASTM A240
	316SS	Finish meets ASTM A240
3M Scotch Seal Metal Sealant 2084	Polyurethane	ASTM E 162, ASTM E 662, Bombardier SP 800-C
Rock River Silicone Sealant	100% Silicone	ASTM C920 Class 25, TT-S-00230C Class A and TT-S-001543A, FDA No 421 CFR 117.2600, conforms to FDA requirements
Red Devil HVAC/R High Temperature Silicone Sealant	Silicone	ASTM C920 Class 25, TT-S-00230C Class A and TT-S-001543A, CEBTP 432.6 140-2, Mil Spec 46106A, CGSB 19C9-9B, DIN 18540 Part 2, OREX 150031-2

**NOTES:**

Reference Nordfab's QF Clamp Technical Data sheet for dimensional, material, and temperature rating information.