

Clamp Hanger 3265-QF

Size (D) In.	Weight Lbs	Galvanized Steel	304SS
		14ga	16ga
3	0.40	Std	Std
4	0.45		
5	0.50		
6	0.60		
7	0.65		
8	0.75		
9	0.85		
10	.95		
11	1.00		
12	1.10		
13	1.20		
14	1.15		
15	1.30		
16	1.35		
17	1.40		
18	1.50		
20	1.80		
22	4.10		
24	5.00		

Temperature Rating of Product Components		
° F	Clamp Hanger	
600°	Galvanized Steel	Optional - 304SS
500°		
390°		
158° (intermittent to 194°)		

Additional Notes
At temperatures ranging between 390° F and 480° F, the zinc-iron alloy layers in galvanized steel will continue to provide a high level of protection from corrosion. However, there may be some peeling, changes in mechanical properties, and reduction in the corrosion protection. Recommended max. service temperature is 390° F.

Compliance / Rating of Product Components		
Product	Material	Compliance / Rating
Clamp Hanger	Galvanized	ASTM A653 with a G-90 rating
	304SS	Finish meets ASTM A240
	316SS	Finish meets ASTM A240

Notes:

- Galvanized clamps are "overlap" design.
- Clamp hangers supplied wth galvanized bridge pin. Small bridge pin with clamp sizes 4" - 6", large pin with 7" and larger size clamps.
- Clamp not to be used as a connection.

