

Rubber Hose, Black 3280

Inside Dia In.	Approx. Weight lbs./ft.	Wall Thickness In.	CL Bend Radius In.	Compression Ratio	Negative Pressure In./hg	Working Pressure PSI
1	.14	N/A	N/A	N/A	N/A	N/A
1.5	.17	.025	1.7	2:1	29	25
2	.24	.025	2	2:1	29	19
2.5	.27	.030	2.5	2:1	29	14
3	.34	.030	3	2:1	29	11
3.5	.39	.030	4	2:1	29	10
4	.50	.030	5.5	2:1	29	9
5	.64	.030	6.5	2:1	17	8
5.5	.71	.030	6.8	2:1	12.5	7
6	.91	.030	6	3:1	11	7
7	1.00	.030	7	3:1	9	5
8	1.04	.030	8	3:1	5.5	4.5
9	1.20	.030	9	3:1	10	4
10	1.60	.030	10	3:1	6.5	4
12	2.00	.030	12	3:1	5	3.8
14	2.40	.030	14	3:1	3	3.2
16	2.80	.030	16	3:1	2.3	2.6
18	3.60	.030	18	3:1	2	2.3
20	4.00	.030	21	3:1	1.5	2
24	6.00	.030	25	3:1	.8	1.75



- Medium weight thermoplastic rubber hose reinforced with a spring steel wire helix
- Technical data based on 2 ft. straight lengths of hose @ 72°
- Temperature rating: -65° to 275°